



EMTRAC

Vehicle Computer Unit ST-9284-N08

Vehicles equipped with the EMTRAC system carry a compact, yet rugged, Vehicle Computer Unit (VCU), which is connected to an omni-directional antenna that receives location data and transmits priority requests to intersections through secure RF communication. The positioning capability is able to track vehicles with precision, and the radio range allows reliable intersection response—even in adverse conditions.



Vehicle
Computer Unit

Features:

- 900 MHz, frequency-hopping spread spectrum radio with secure, 256-bit AES encryption
- Typical transmission range of 3,600 feet, enabling intersection-approach zones of the same length
- Integrated computer board contains ultra-fast processor and superior memory, while the MicroSD-card offers vast activity-log storage capability
- Capable of communication through Ethernet, RS-232, or wireless connection
- Supports up to 16 inputs or outputs in any combination
- Capable of storing up to 5,000 intersection-approach zones
- Ability to monitor multiple inputs to prompt priority requests, including emergency light-bar, bus-door or pull-cord activity, schedule adherence, and passenger count
- Time-out feature configurable to cease priority requests after designated amount of no-motion time
- Programmable with Windows XP, Vista, 7, 8, 10 (or later) operating systems

Specifications:

| Vehicle Computer Unit | |
|--|--|
| VCU: | 2.35" (H) x 4.75" (W) x 8.5" (D) |
| Antenna: | 1.15" (H) x 4.55" (Diameter) |
| 15-ft cable provided; additional cable available | |
| Weight: | VCU - 2.1lbs (950g) Antenna - 1.1lbs (500g) |
| Power: | 10 to 37.5 VDC, 2A max |
| Temp: | -34°C (-30°F) to +74°C (+165°F) |
| Humidity: | 5% to 95% Relative |

Navigation Engine

| Parameter | Specification |
|-------------------------|-----------------------------------|
| Receiver Type: | 72-channel, GPS/GLONASS/WAAS |
| Navigation Update Rate: | 4 Hz Max, 1 Hz (w/Dead Reckoning) |
| Accuracy: | Position 2.0 m CEP |
| Sensitivity: | Tracking -160 dBm |
| | Cold Starts -147 dBm |
| | Hot Starts -156 dBm |
| Heading Accuracy: | 0.5 degrees |
| Operational Limits: | Velocity 1,640 ft/sec [500 m/s] |

UHF Radio (Typical Performance)

| Performance | Standard Range |
|-------------------------|--------------------------|
| Transmit Power Options: | 1mW - 1 Watt |
| Urban Range: | 3,600 ft (1100 m) |
| Interface Data Rate: | 1,200 - 230,400 bps |
| RF Data Rate: | 9,600 bps to 115,200 bps |
| Receiver Sensitivity: | -110 dBm to -100 dBm |

All specifications are subject to change without notice.

Radio, Security, and Networking

| | |
|------------------|---|
| Frequency: | 902 - 928 MHz |
| Spread Spectrum: | Frequency-Hopping Spread Spectrum |
| Modulation: | FSK (Frequency Shift Keying) |
| Certifications: | FCC (Part 15.247), Industry Canada (IC) |
| Encryption: | 256-bit AES |
| Data Comm.: | Ethernet 100Base-T or Serial (RS-232) |